

S3E Stump Pro 25HP Self-Propelled Stump Grinder

New · Stump Grinders · 25–50hp · S3E



PRICE

\$19,500

+ GST

TALK TO US

1300 241 132

sales@eliteequipt.com

KEY FEATURES

Gets into tight access

At 28 inches total width it fits through standard side gates and down narrow paths, reaching stumps larger machines cannot.

Honda iGX800 commercial power

25hp fuel-injected V-twin with a built-in hour meter and oil warning light, so low oil is flagged before it becomes damage.

Centre pivot design

The machine pivots about its centre for a smoother, more controlled side-to-side sweep across the stump and a more even cut.

Ogura electromagnetic clutch

Engages the cutter wheel electrically rather than by belt tensioning — less vibration and one less wear item to adjust.

Donaldson air filtration

Heavy-duty filtration on a machine that works in its own dust and chip stream, protecting the engine and extending its life.

Free wheeling hubs

Disengage the drive and reposition by hand — into a trailer, around an obstacle, or into a corner too tight to drive into.

AT A GLANCE

25 hp

18.6 kW

Rated power

28 in

711 mm

Total width

14 in

356 mm

Cutting depth below grade

35 in

889 mm

Cutting width (arc)

595 lb

270 kg

Operating weight

FULL SPECIFICATIONS 25 published figures

ENGINE & POWER

Engine	Honda iGX800 V-twin	
Rated power	25 hp	18.6 kW
Fuel system	Electronic fuel injection (FI)	
Fuel	Unleaded petrol	
Air filtration	Donaldson air filter system	
Engine monitoring	Built-in hour meter + oil warning light	

DRIVELINE

Cutter wheel drive	12 V Ogura electromagnetic clutch	
Drive	Self-propelled, hydraulic	
Wheel hubs	Free wheeling	

CUTTING

Cutting depth below grade	14 in	356 mm
Cutting height above grade	14 in	356 mm
Cutting width (arc)	35 in	889 mm
Cutter wheel thickness	1.32 in	33.5 mm
Cutter teeth	8 × Green Teeth 700	
Cutter wheel shaft	12 in	305 mm
Cutter wheel shaft diameter	1.44 in	36.6 mm

DIMENSIONS & WEIGHT

Operating weight	595 lb	270 kg
Overall length	6 ft 4 in	1,930 mm
Overall height	4 ft 2 in	1,270 mm
Total width	28 in	711 mm

MACHINE

Condition	New	
Frame	Centre pivot design	
Control arm	Swinging	
Operator safety	Wrist-strappable kill switch	
Origin	Built in West Virginia, USA	



Side profile



Front three-quarter — cutter wheel guard



Front three-quarter



Side view



Side view



Front three-quarter



Three-quarter view



Control arm extended



Rear three-quarter



Rear view



Operator position — swinging control arm



Engine bay — Donaldson air filtration



Honda iGX800 — fuel-injected V-twin



Controls — forward / reverse and kill switch



Cutter wheel and guard



Centre pivot — daily grease point



In work