

YUCHAI

U60

Yuchai U60 5.6Ton Excavator

NEW ■ EXCAVATORS ■ 2-5.9T (MINI)

\$80,289

AUD inc. GST



WEIGHT

5600 kg

POWER

46 hp

DIG DEPTH

3635 mm

BUCKET

0.18 m³

SPECIFICATIONS

Engine	V2607 (Euro V / Tier 4F) / V2403 (Euro III A)	Standard Bucket Width	742mm
Rated Power	46hp	Walking Speed	2.2 / 3.6 km/h
Digging Depth	3635mm	Swing Speed of Platform	9.2 rpm
Width	1960mm	Auxiliary Flow	110 l/m
Weight	5600kg	Boom Swing Angle (Left/Right)	53° / 70°
Standard Bucket Capacity	0.18m ³		

OVERVIEW

The U60 is a 4th generation 6 Ton excavator from Yuchai Heavy Industries. Powered by a class leading 47hp Kubota diesel engine matched to a high flow, load sensing piston pump and quality main control valve for powerful yet smooth hydraulic operation. The U60 is a full featured excavator with approved A/C ROPS cabin, swing boom, bi-directional piping and front blade. Take a close look at the Yuchai difference, the U60 offers an extra large, fully approved ROPS a/c cabin and full width rear door for easy access to maintenance items. Safety systems such as crane valves, movement alarm, flashing light and Australian OH&S compliant hitches all come standard with dual auxiliary piping with electro-proportional hand controls ready for tilt quick hitches and rotating grabs. YUCHAI Heavy Industry Co. Ltd. was founded in 1989 and they were the first enterprise in China to produce mini-excavators and sell them to the world. With more than 30 years of innovation and development experience you can be assured you are buying a high-quality machine with exceptional support and user experience.

STANDARD SPECIFICATION

- ✓ **Kubota Engine**
Powered by a V2607 (Euro V / Tier 4F) / V2403 (Euro III A) rated at 46hp.
- ✓ **2 Speed Travel**
Two-speed travel motors — 2.2 / 3.6 km/h.
- ✓ **A/C Cabin**
Air-conditioned cabin fitted as standard.
- ✓ **Hammer / Auger Piping**
Auxiliary hydraulic piping fitted as standard, 110 l/m auxiliary flow, for hammers, auger drives and grabs.

1300 241 132

sales@eliteequipt.com

Unit 4/5-7 Graham St, Underwood QLD 4119

ABN 29 509 705 048 · eliteequipt.com

E&OE. Specifications subject to change without notice.

FULL SPECIFICATION

32 published figures – manufacturer's data

BASIC

Machine weight	5600 kg
Bucket capacity	0.18 m ³
Bulldozer blade	1960 × 420 mm

PERFORMANCE

Engine	Kubota
Engine model	V2607 (Euro V / Tier 4F) / V2403 (Euro III A)
Engine power	35/2200 / 30.7/2200 kW/rpm
Max. gradeability	35 °
Max. digging force of arm	26 kN
Max. digging force of bucket	45 kN
Traveling speed	3.6/2.2 km/h
Max. hauling force	46.5 kN
Slewing speed of platform	9.2 rpm

OPERATING RANGE

Max. digging height	5670 mm
Max. digging depth	3635 mm
Max. digging radius	6190 mm
Max. digging radius on ground level	6055 mm
Max. dumping height	4015 mm
Min. slewing radius	2550 mm
Max. vertical digging depth	2985 mm

TRANSPORT DIMENSIONS

Overall length	5545 mm
Overall width	1960 mm
Overall height	2550 mm

OTHER

Chassis width	1960 mm
Length of track	2500 mm
Width of track	400 mm
Ground clearance of undercarriage	310 mm
Ground clearance of platform	625 mm
Platform tail turning radius	1065 mm
Length to centre of rollers	1990 mm
Steering head angle	70 (L) / 53 (R) °
Fuel tank capacity	73 L
Hydraulic oil tank capacity	70 L

WORKING RANGE
TRANSPORT DIMENSIONS

millimetres

