

YUCHAI

YC230LC-9

Yuchai YC230LC-9 23Ton Excavator

NEW ■ EXCAVATORS ■ 20-29.9T

\$203,500

AUD inc. GST



WEIGHT

23100 kg

POWER

166 hp

DIG DEPTH

6625 mm

BUCKET

1.08 m³

SPECIFICATIONS

Engine	Cummins QSB7	Standard Bucket Width	1340mm
Rated Power	166hp	Walking Speed	3.4 / 5.2 km/h
Digging Depth	6625mm	Swing Speed of Platform	13-15 rpm
Width	2990mm	Auxiliary Flow	215l/m
Weight	23100kg	Boom Swing Angle (Left/Right)	—
Standard Bucket Capacity	1.08m ³		

OVERVIEW

The YC230LC-9 is a powerful 23-Ton excavator designed for heavy-duty operations. Equipped with a Cummins engine, it delivers exceptional performance and reliability, ensuring efficient handling of demanding tasks. The long carriage design provides enhanced stability, making it ideal for tough terrains and large-scale projects. With its conventional tail swing, this excavator offers excellent manoeuvrability without compromising on digging power. Featuring an all-Japanese hydraulic system, the YC230LC-9 ensures precise control and smooth operation, enhancing productivity on job sites. Built to last, its robust construction and advanced engineering make it a dependable choice for industries such as construction, mining, and earthmoving. Whether for excavation or material handling, the YC230LC-9 excels in delivering consistent, high-quality performance.

STANDARD SPECIFICATION

- ✓ **Cummins Engine**
Powered by a Cummins QSB7 rated at 166hp.
- ✓ **2 Speed Travel**
Two-speed travel motors — 3.4 / 5.2 km/h.
- ✓ **A/C Cabin**
Air-conditioned cabin fitted as standard.
- ✓ **Hammer / Auger Piping**
Auxiliary hydraulic piping fitted as standard, 215l/m auxiliary flow, for hammers, auger drives and grabs.

1300 241 132

sales@eliteequipt.com

Unit 4/5-7 Graham St, Underwood QLD 4119

ABN 29 509 705 048 · eliteequipt.com

E&OE. Specifications subject to change without notice.

FULL SPECIFICATION

29 published figures – manufacturer's data

BASIC

Machine weight	23100 kg
Bucket capacity	1.08 m ³
Width of bucket	1340 mm

PERFORMANCE

Engine model	Cummins QSB7
Engine power	124/2050 kW/rpm
Gradeability	35 °
Max. digging force of arm	102 kN
Max. digging force of bucket	139.3 kN
Traveling speed	3.4/5.2 km/h
Slewing speed of platform	13-15 rpm

OPERATING RANGE

Max. digging height	9725 mm
Max. digging depth	6625 mm
Max. digging radius	9890 mm
Max. digging radius on ground level	9725 mm
Max. dumping height	6815 mm
Min. slewing radius	3410 mm
Max. vertical digging depth	6040 mm

TRANSPORT DIMENSIONS

Overall length of transportation	9695 mm
Overall width	2990 mm
Overall height	3115 mm

OTHER

Width of undercarriage	2990 mm
Length of track	4450 mm
Width of track	600 mm
Min. ground clearance	470 mm
Height between platform and ground	1070 mm
Platform tail turning radius	2945 mm
Wheel base	3655 mm
Fuel tank capacity	350 L
Hydraulic oil tank capacity	210 L

WORKING RANGE
TRANSPORT DIMENSIONS

millimetres

