

YUCHAI

YC85-9

Yuchai YC85-9 8.5Ton Excavator

NEW ■ EXCAVATORS ■ 6-9.9T (MIDI)

\$93,489

AUD inc. GST



WEIGHT

8500 kg

POWER

74 hp

DIG DEPTH

4160 mm

BUCKET

0.32 m³

SPECIFICATIONS

Engine	Yanmar 4TNV98T	Standard Bucket Width	875mm
Rated Power	74hp	Walking Speed	2.9 / 4.3 km/h
Digging Depth	4160mm	Swing Speed of Platform	10-13 rpm
Width	2260mm	Auxiliary Flow	80 l/m
Weight	8500kg	Boom Swing Angle (Left/Right)	—
Standard Bucket Capacity	0.32m ³		

OVERVIEW

Yuchai yc85-9 8.5Ton conventional tail swing excavator is powered by a Yanmar engine and all Japanese hydraulic system. Stepping into the YC85-9 the first thing you notice is the king sized air conditioned cabin with plenty of operator space and excellent forward and side visibility. The controls are smooth and accurate and the colour LCD display is easily visible in all lighting conditions. Maintenance has been made super easy on the YC85-9 with an extra large rear hood and 2 side doors that open up to expose the entire engine compartment. Front hatches open up access to the main hydraulic valve and batteries. Take a close look at the Yuchai difference, safety systems such as movement alarm, flashing light and Australian OH&S compliant hitches all come standard with the option to upgrade to dual auxiliary piping with electro-proportional hand controls for tilt quick hitches and rotating grabs. YUCHAI Heavy Industry Co. Ltd. was founded in 1989 and they were the first enterprise in China to produce mini-excavators and sell them to the world.

STANDARD SPECIFICATION

- ✓ **Yanmar Engine**
Powered by a Yanmar 4TNV98T rated at 74hp.
- ✓ **2 Speed Travel**
Two-speed travel motors — 2.9 / 4.3 km/h.
- ✓ **A/C Cabin**
Air-conditioned cabin fitted as standard.
- ✓ **Hammer / Auger Piping**
Auxiliary hydraulic piping fitted as standard, 80 l/m auxiliary flow, for hammers, auger drives and grabs.

1300 241 132

sales@eliteequipt.com

Unit 4/5-7 Graham St, Underwood QLD 4119

ABN 29 509 705 048 · eliteequipt.com

E&OE. Specifications subject to change without notice.

FULL SPECIFICATION

30 published figures – manufacturer's data

BASIC

Machine weight	8500 kg
Bucket capacity	0.32 m ³
Width of bucket	875 mm

PERFORMANCE

Engine model	Yanmar
Engine power	56.5/2200 kW/rpm
Gradeability	35 °
Max. digging force of arm	41 kN
Max. digging force of bucket	56 kN
Traveling speed	2.9/4.3 km/h
Max. hauling force	68 kN
Slewing speed of platform	10~13 rpm

OPERATING RANGE

Max. digging height	7140 mm
Max. digging depth	4160 mm
Max. digging radius	6630 mm
Max. digging radius on ground level	6491 mm
Max. dumping height	5100 mm
Min. slewing radius	2144 mm
Max. vertical digging depth	3588 mm

TRANSPORT DIMENSIONS

Overall length of transportation	6425 mm
Overall width	2260 mm
Overall height	2705 mm

OTHER

Width of undercarriage	2150 mm
Length of track	2783 mm
Width of track	450 mm
Height between undercarriage and ground	380 mm
Height between platform and ground	790 mm
Platform tail turning radius	1881 mm
Track gauge	2200 mm
Fuel tank capacity	151 L
Hydraulic oil tank capacity	125 L

WORKING RANGE
TRANSPORT DIMENSIONS

millimetres

